

## Armourbase Pro – 30m

Edition: 08/06/2011

### APPLICATION

*Schingle underlayment*

### COMPOSITION

*Top coating* : *Polypropylene*  
*Inlay* : *Polyester*  
*Bottom coating* : *Polypropylene*

### FINISHING

*Top side:* *Green printed polyprop – IKO label*  
*Bottom side:* *Polypropylene, black*

### DIMENSIONS

*Length:* *30 x 1 m*  
*Thickness:* *0,5 mm*  
*Weight/roll:* *± 11,4 kg*

### PACKAGING

*Rolls / Palette:* *40*

### TECHNICAL INFO

	<i>Tensile strength</i>		<i>Elongation at break</i>		<i>Nail tear</i>	
	<i>Longitudinal</i>	<i>Traverse</i>	<i>Longitudinal</i>	<i>Traverse</i>	<i>Longitudinal</i>	<i>Traverse</i>
<i>Minimal value</i>	$\geq 400N$	$\geq 345N$	$\geq 25\%$	$\geq 25\%$	$\geq 130N$	$\geq 130N$
<i>Cold Bend</i>	<i>- 45°C</i>					
<i>SD-value</i>	<i>20m</i>					
<i>UV- stability</i>	<i>4 months</i>					