

Technical Data Sheet

KUNOS Maintenance No. 1878

N means **LIVOS neutral** for the allergy-prone and chemically sensitive

Application range	In the interior, as protection and maintenance of surfaces treated with KUNOS oils (No. 240 – 245) as well as SAMO No. 698, e.g. kitchen countertops, tables and floors. Not suitable for stained wood or cabinet interior surfaces.
Technical qualities	Free of terpenes and cobalt. Produces a satin-glossy surface after the treatment. Complies with the German Industrial Norm DIN 53 160 for color fastness when exposed to perspiration and saliva. Suitable for toys according to DIN EN 71 Part 3.
Full declaration	Isoaliphates, linseed oil - stand oil - natural resin ester, castor oil - natural resin ester, wood oil, linseed oil, natural resin glycerol ester, micronized wax, silica, dehydrated amino sugar, carnauba wax, shellac wax, beeswax, walnut oil and drying agents free of lead (Mn, Zr).
Colors	Clear 002
Dilution	Ready to use.
Application method	With a lint-free cotton cloth or single disc rotary machine and felt pad, at temperatures above 15°C (59°F).
Coverage	To be determined by a test application. Approximately 10 ml/m ² , could be considerably more or less, depending on the absorbency and condition of the KUNOS-surface.
Cleaning	Clean equipment immediately after use with LEVO Brush Cleaner No. 997.
Drying time	At 23°C (73 °F) and 50% relative humidity: 4 - 8 hours.
Specific gravity	Approximately 0.87 g/ml.
Safety advice	<p>Ensure good ventilation during and after application. Always be sure to store and then dispose of cleaning cloths, polishing pads, sponges, etc. that are still wet or even slightly moist with KUNOS Maintenance No. 1878 in an airtight metal container or in water, as there is a danger of spontaneous combustion caused by the plant oil content. The product itself will not combust spontaneously.</p> <p>P102 Keep out of reach of children. P301+P310 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a doctor. EUH066 Repeated exposure may cause skin dryness or cracking.</p>
Disposal	According to locally regulated laws.
Container sizes	0.25 l; 0.75 l; 2.5 l.
Storage	Cool and dry. Shelf life: unopened at least 4 years. Transfer unused product into smaller container for storage in order to minimize excess air.

How to use

KUNOS Maintenance No. 1878

- Preparation** The KUNOS surface to be maintained must be dry, clean and dust-free. Deep scratches and damages should be eliminated with the initial treatment product.
- Application** Stir thoroughly before use. Remove possible skin formed on surface.
Test application!
Apply KUNOS Maintenance dropwise (approx. 5 – 10 g/m²) on the surface to be maintained, and polish immediately with little pressure using a single disc rotary machine and felt pad or a lint-free cotton cloth. Avoid streak formation. Check in the backlight.
You may repeat the process.
- Cleaning
Care** Clean with TRENA pH-Neutral Cleaner No. 556 added to water, and wipe moist but not wet.
After-treatment with KUNOS Maintenance No. 1878, depending on the use several times a year.
- Important tips** If a coarse-grained abrasive pad is used with a single disc rotary machine to polish KUNOS Maintenance, the color intensity of an existing pigmented coating might decrease or the oil-resin coating could be removed.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at www.livos.de. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.

March 2017